

## OEM Approved

Copeland® and Other Compressor and Equipment Manufacturers

ZEROL® 200TD is highly recommended for use with R-22 as well as with HCFC service blends and other HCFC and CFC refrigerants in refrigeration and air conditioning applications.

Keep container tightly closed to maintain dryness of contents. Refrigeration oils can absorb moisture from the air.

### REFRIGERATION OIL RECOMMENDATION CHART

| OEM                | Refrigerant    | Zerol Product*   |
|--------------------|----------------|------------------|
| Bitzer             | R-22 & Blends* | Zerol 150, 300   |
| Bristol            | R-22 & Blends  | Zerol 150        |
| Bock               | R-22 & Blends  | Zerol 150, 500   |
| Carrier            | R-22 & Blends  | Zerol 300, 400CA |
| Carlyle            | R-22 & Blends  | Zerol 150        |
| Danfoss            | R-22 & Blends  | Zerol 150        |
| Dorin              | R-22 & Blends  | Zerol 150, 200TD |
| Emerson (Copeland) | R-22 & Blends  | Zerol 200TD, 300 |
| Johnson Controls   | R-22 & Blends  | Zerol 300        |
| Sabroe             | R-22 & Blends  | Zerol 150, 300   |
| Tecumseh           | R-22 & Blends  | Zerol 150, 300   |
| Thermoking         | R-22 & Blends  | Zerol 150        |
| Bock               | Ammonia        | Zerol 150, 500   |
| Mycom (Mayekawa)   | Ammonia        | Zerol 300        |

\* Blends include: R-401A & B, R-402A & B, R-403B, R-408A, R-409A, R-414B, R-500, R-502. Zerol products are also suitable for R123 and R-124.

† For other Zerol product options not listed, contact Nu-Calgon.

4308-01



Shrieve

# ZEROL® 200TD

## Alkylbenzene Refrigeration Oil

Viscosity 200 SUS at 100° F (ISO 46)

**Copeland Approved**

High Solubility, Dependable Lubrication

Excellent Thermal Stability and Compatibility

Controlled Foaming

Nu-Calgon

### APPLICATION:

ZEROL® 200TD is recommended for use with refrigerants R-401a/R-401b (MP39/MP66) and R-402a/R-402b (HP80/HP81) as well as other HCFC and CFC refrigerants in field service and retrofit applications. Follow the compressor manufacturer's and OEM equipment manufacturer's recommendations.


CAUTION: KEEP OUT OF REACH OF CHILDREN.

DO NOT weld, heat or drill container. Residue may ignite with explosive violence if heated sufficiently.

Manufactured by Shrieve Chemical Products, Inc. The Woodlands, TX.

ZEROL® is a trade mark owned and used by The Shrieve Group of Companies.

Copeland is a registered trademark of Emerson Climate Technologies.



MADE IN THE  
**USA**

Nu-Calgon  
2611 Schuetz Rd.  
St. Louis, MO 63043  
Customer Service: 800-554-5499  
Chemical Emergency: 800-424-9300  
www.nucalgon.com  
(718) Calgon is a licensed trade name.

55 U.S. Gallons (208.18 Liters)