

This fast drying formulation leaves no residue and is compatible with plastic components and painted surfaces if overspray occurs. This next generation product contains no CFC's, HCFC's, or other ozone depleters. Blasting spray easily cleans oil, flux, dirt, and other contaminants from contacts, printed circuit boards, switches, motors, precision instruments and more. While advanced in performance and ozone safety, this product is flammable and must therefore be used only on de-energized components and equipment. Always allow to dry and evacuate fumes before power is returned.

DIRECTIONS FOR USE:

This product must be used in accordance to the following directions by HVACR professionals only.

For the cleaning of fairly large surfaces, aim the spray tip at the area to be cleaned and press button. For the cleaning of confined areas and small exact spots, press the 6" extension tube into the valve opening until it bottoms, then spray directly on the spot to be cleaned.



DANGER

HAZARD STATEMENT - Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. May cause genetic defects. Suspected of damaging fertility or the unborn child. May cause cancer.

PRECAUTIONARY STATEMENT - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves, protective clothing, eye protection and face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing vapours. Use only outdoors or in a well-ventilated area.

IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.

IF INHALED: remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

IF exposed or concerned: Get medical attention. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up. Keep container tightly closed. Dispose of container in accordance with local, regional, national and international regulations.

WARNING: This product can expose you to chemicals including benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NOTE: Sudden temperature drop can result in "thermal shock" which may cause crazing of some sensitive plastics. While overspray is compatible with plastic components and painted surfaces, always test in an inconspicuous area before general use if compatibility of specific plastic composition is uncertain. Accumulated vapors from this product may reach ignition conditions in confined spaces. Always use with adequate ventilation.

IMPORTANT: This product is different from CFC/HCFC products and is **FLAMMABLE**. Always use on de-energized components and equipment. Always allow to dry and evacuate fumes before power is returned. Always test in an inconspicuous area to check product for compatibility.

CONTAINS (CAS #): Difluoroethane 75-37-6; Benzene 71-43-2; Ethylbenzene 100-41-4; Cumene 98-82-8; Heptane 142-82-5; Heptane, Branched, Cyclic And Linear 426260-76-6; Naphtha, petroleum, hydrotreated light 64742-49-0; Naphthalene 91-20-3; Solvent naphtha, petroleum, light aliphatic 64742-89-8; Toluene 108-88-3.

VOC Category and Limit: Electrical Cleaner 45%.

Made in the U.S.A.
Nu-Calgon
2611 Schuetz Rd.
St. Louis, MO 63043
Customer Service: 800-554-5499
Chemical Emergency: 800-424-9300
www.nucalgon.com

(1118) Calgon is a licensed trade name.



4082-03

Electrical Contact Cleaner

CONTACT CLEANER

High Solvency Cleaning Power

**Leaves No Residue, Dries Fast
Plastic Component Compatible**



**360° Valve Sprays
in Any Position**

DANGER:

**EXTREMELY
FLAMMABLE.
MAY BE FATAL IF
SWALLOWED.
SKIN IRRITANT.
CONTENTS UNDER
PRESSURE.**

- KEEP OUT OF REACH
- OF CHILDREN.
- See back panel for
- additional precautionary
- statements.
- **FOR PROFESSIONAL**
- **USE ONLY**

NET WT. 11 OZ. (312 GRAMS)